

EUROVAC II 2.5HP & 5HP CENTRAL DETAIL VACUUM SYSTEMS



Eurovac II Central High Vacuum Detail Systems are an ideal and affordable solution for one or two users with a longest pipe run of 100'

- Powerful 2.5HP – 1 or 2 motor provides excellent suction and vacuum performance.
- Superior Filtration: Cyclonic filtration removes virtually all of the particulate before the secondary bag filters.
- Muffler and insulated motor housing reduce noise level to 70 dBA.
- Properly engineered piping system graduating from 3" to 2" will maintain optimum velocity and reduce friction losses.
- On/Off toggle switches conveniently located at each drop with a run timer set to shut the system down after a period of time.
- Mounting Options: Systems include floor mount tabs with optional wall/post mounting bracket available upon request.

Available Upgrades:

Brushless Motors, Dome Lid, Stainless Steel Construction, Coin, Token, or Credit Card Acceptor, including Apple Pay and Google Pay

Technical Data:

Model Number	SYS-050-164BS0L0	SYS-050-0080L00
Horse Power	2.5HP	5HP
Voltage	1 Phase 60 Hz	
Power	115 volts	125/250 volts
Current Draw	13 amps	13 amps x 2
Circuit Required	15 amps	15 amps x 2
Airflow (max.)	142 CFM	284 CFM
Pressure (max.)	146"	
Sound Level @ 10'	70 dB(A) @ 3 meters	
Canister Size	10 gallon plastic tote	
Filter Area	Four (4) Bag Filters - 16 ft ²	



For more information, contact Eurovac:

CANADA and USA
Toll-Free 800-265-3878 / Fax 416-744-8079
info@eurovac.com

44 Milvan Dr., North York, ON M9L 1Z3
5927 Center Rd, Unit 3, Valley City, OH 44039