



Airlines (Work Hoses)

Work Hose Airlines	Eurovac Part No.	Description
		WORK HOSE AIRLINE REPLACEMENTS Does Not Include: <ul style="list-style-type: none"> Quick Disconnects (see below for additions)
	HOS-A02-005P2M2M	1/4" x 5' Blue Airline w/ 1/4" MPT Ends
	HOS-A02-010P2M2M	1/4" x 10' Blue Airline w/ 1/4" MPT Ends
	HOS-A02-015P2M2M	1/4" x 15' Blue Airline w/ 1/4" MPT Ends
	HOS-A02-020P2M2M	1/4" x 20' Blue Airline w/ 1/4" MPT Ends
	HOS-A02-025P2M2M	1/4" x 25' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3705P14M	3/8" x 5' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3710P14M	3/8" x 10' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3715P14M	3/8" x 15' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3720P14M	3/8" x 20' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3723P14M	3/8" x 23' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3725P14M	3/8" x 25' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3730P14M	3/8" x 30' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3735P14M	3/8" x 35' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3740P14M	3/8" x 40' Blue Airline w/ 1/4" MPT Ends
	HOS-EUR-3750P14M	3/8" x 50' Blue Airline w/ 1/4" MPT Ends
	Airline Per Foot	Eurovac Part No.
		BLUE AIRLINE Equipment Specs: <ul style="list-style-type: none"> Full reel is 500'
	HOS-AIR-0250BL00	Work Hose Airline - 1/4" Blue - Per Ft.
	HOS-AIR-0375BL00	Work Hose & Drop Down Airline - 3/8" Blue - Per Ft.
Y Fitting w/ Leads	Eurovac Part No.	Description
		DOUBLE AIRLINE "Y" Includes: <ul style="list-style-type: none"> Quick Disconnects
	SYS-030-590Y0000	Y Fitting With Leads 30-590 Airline










Airline Fittings



Airline Fittings	Eurovac Part No.	Description
AIRLINE FITTINGS		
	HOS-DJI-DC2MS000	1/4" MPT Safety Disconnect (Male Fitting) Features: <ul style="list-style-type: none"> • Accept 1/4 INDUSTRIAL type plugs (A-A59439) • Prevent the risk of dangerous hose whip or accidental disconnection • Non-marring coupler body prevents scratching of delicate surfaces • Swivel body allows quick installation and optimal positioning • 1 push safe disconnection • Downstream pressure is automatically vented and disconnection is easily performed at zero pressure • Disconnection noise level of only 80 dB Equipment Specs: <ul style="list-style-type: none"> • Body: Anti-static polyester composite • Weight: 73 g • Airflow: 34 SCFM at 100 PSIG inlet with 10 PSIG pressure drop • Maximum Working Pressure: 174 PSI • Temperature range: -15 °C to 70 °C • Connection: 1/4 (F) NPT
	HOS-DJI-DC200000	1/4" FPT Disconnect (Female Fitting) <ul style="list-style-type: none"> • For 1/4" & 3/8" Blue Airline Hose
	HOS-DJI-DC210000	1/4" MPT Disconnect (Male Fitting) <ul style="list-style-type: none"> • For Pendant Drops
	HOS-DJI-DCP20000	1/4" FPT Nipple For Disconnect (Male Fitting) <ul style="list-style-type: none"> • For 1/4" Clear & 3/8" Blue Airline Hose
	HOS-DJI-DCP21000	1/4" MPT Nipple For Disconnect <ul style="list-style-type: none"> • For Tool Connection to Hose (no whip hose)
	TOO-AVT-14BALLSW	1/4" Barb x 1/4" MPT Ball Swivel Fitting
	TOO-AVT-14SWIVEL	1/4" MPT x 1/4" FPT Aluminum Swivel
	HOS-BBR-00040M04	1/4" ID Hose x 1/4" MPT Hose Barb Brass <ul style="list-style-type: none"> • For 1/4" Blue Airline Hose
	HOS-BBR-00060M04	3/8" ID Hose x 1/4" MPT Hose Barb Brass <ul style="list-style-type: none"> • For 3/8" Blue Airline Hose
	HOS-FBL-05251003	.525" Brass Hose Ferrule <ul style="list-style-type: none"> • For 1/4" Blue Airline Hose
	HOS-FBL-06501305	.650" Brass Hose Ferrule <ul style="list-style-type: none"> • For 3/8" Blue Airline Hose
	HOS-CGE-0SCG0006	HS-6 Gear Clamp .375" to .875" OD Hose

Air Tubing

Poly Tubing	Eurovac Part No.	Description
		POLYETHYLENE TUBING Equipment Specs: <ul style="list-style-type: none"> • Outside: UV Rated Application: <ul style="list-style-type: none"> • Pulse Jet Cleaning - From Solenoid Valve to Solenoid Ass'y • VFD's - From Separator Port to Pressure Transducer • Transit Dumpster Lids - This is when both colors are needed
	HOS-TN6-J081000J	1/4"OD Black Polyethylene Tubing 100' Reel - per ft.
	HOS-TN6-J08B500J	1/4"OD Black Polyethylene Tubing 500' Reel - per ft.
	HOS-TN6-J081R00J	1/4"OD Red Polyethylene Tubing 100' Reel - per ft.
	HOS-TN6-J08R500J	1/4"OD Red Polyethylene Tubing 500' Reel - per ft.

Aluminum Compressed Air Pipe & Fittings



Aluminum Compressed Air Pipe & Fittings	Eurovac Part No.	Description
		ALUMINUM COMPRESSED AIR PIPE & FITTINGS
	COM-TUB-01600400	16mm (.63") x 4m (13.12') Aluminium Compressed Air Pipe
	COM-TUB-04000600	40mm (1.57") x 6m (19.68') Aluminium Compressed Air Pipe
	COM-UNI-04004000	40mm (1.57") Union Aluminium for Compressed Air Pipe
	COM-ELB-01609000	16mm (.63") 90 Elbow Aluminium for Compressed Air Pipe
	COM-ELB-04009000	40mm (1.57") 90 Elbow Aluminium for Compressed Air Pipe
	COM-ELB-01604500	16mm (.63") 45 Elbow Aluminium for Compressed Air Pipe
	COM-TEE-04004000	40mm (1.57") Tee Aluminium for Compressed Air Pipe
	COM-CAP-04000000	40mm (1.57") End Cap for Compressed Air Pipe
	COM-HNG-04000000	40mm (1.57") Swivel Loop Hanger for Compressed Air Pipe
	COM-CON-04000120	40mm (1.57") x 1-1/2" (F)NPT Connector for Compressed Air Pipe
	COM-MTC-01600000	16mm (.63") Mounting Clip for Compressed Air Pipe

	COM-TKO-04001600	40mm (1.57") x 16mm (.63") Aluminum Take-Off Drop for Compressed Air Pipe
	COM-MNF-01600000	16mm (.63") Manifold W/Quick Coupler & BV for Compressed Air Pipe

Chemical Dispensing Tubing

Nylon Tubing	Eurovac Part No.	Description
		NYLON TUBING Equipment Specs: <ul style="list-style-type: none"> • Type: 12 • Amount per Reel: 100' • 3/8" Tubing: Standard Product Used For Water Based Chemicals • 1/2" Tubing: Standard Product Used For Thicker Chemicals (ie: Waxes) Application: <ul style="list-style-type: none"> • Central Systems - From CDC to Chemical Drops
	HOS-TN6-C121000J	3/8"OD Red Nylon Tubing - per ft.
	HOS-TN6-D121000J	3/8"OD Blue Nylon Tubing - per ft.
	HOS-TN6-F121000J	3/8"OD Yellow Nylon Tubing - per ft.
	HOS-TN6-G121000J	3/8"OD Orange Nylon Tubing - per ft.
	HOS-TN6-E121000J	3/8"OD Neon Green Nylon Tubing - per ft.
	HOS-TN6-B121000J	3/8"OD Black Nylon Tubing - per ft.
	HOS-TN6-H121000J	3/8"OD Grey Nylon Tubing - per ft.
	HOS-TN6-I121000J	3/8"OD White Nylon Tubing - per ft.
	HOS-TN6-J121000J	3/8"OD Green Nylon Tubing - per ft.
	HOS-TN6-K121000J	3/8"OD Neon Pink Nylon Tubing - per ft.
	HOS-TN6-L121000J	3/8"OD Purple Nylon Tubing - per ft.
	HOS-TN6-A121000J	3/8"OD Clear Nylon Tubing - per ft.
	HOS-TN6-M121000J	3/8"OD Neon Orange Nylon Tubing - per ft.
	HOS-TN6-N121000J	3/8"OD Neon Yellow Nylon Tubing - per ft.
	HOS-TN6-O121000J	3/8"OD Light Grey Nylon Tubing - per ft.
	HOS-TN6-C161000J	1/2"OD Red Nylon Tubing - per ft.
	HOS-TN6-D161000J	1/2"OD Blue Nylon Tubing - per ft.
	HOS-TN6-F161000J	1/2"OD Yellow Nylon Tubing - per ft.
	HOS-TN6-G161000J	1/2"OD Orange Nylon Tubing - per ft.
	HOS-TN6-E161000J	1/2"OD Neon Green Nylon Tubing - per ft.
	HOS-TN6-B161000J	1/2"OD Black Nylon Tubing - per ft.




	HOS-TN6-H161000J	1/2"OD Grey Nylon Tubing - per ft.
	HOS-TN6-I161000J	1/2"OD White Nylon Tubing - per ft.
	HOS-TN6-J161000J	1/2"OD Green Nylon Tubing - per ft.
	HOS-TN6-K161000J	1/2"OD Neon Pink Nylon Tubing - per ft.
	HOS-TN6-L161000J	1/2"OD Purple Nylon Tubing - per ft.
	HOS-TN6-A161000J	1/2"OD Clear Nylon Tubing - per ft.
	HOS-TN6-M161000J	1/2"OD Neon Orange Nylon Tubing - per ft.
	HOS-TN6-N161000J	1/2"OD Neon Yellow Nylon Tubing - per ft.
	HOS-TN6-O161000J	1/2"OD Light Grey Nylon Tubing - per ft.
Twin Bonded Polyurethane Tubing	Eurovac Part No.	Description
		TWIN BONDED POLYURETHANE TUBING Application: • Return & Fed Line For Extractor Hoses
	HOS-TPU-J102000J	1/4"OD Twin Bonded Blue/Red Polyurethane Tubing - per ft.
Clear Reinforced PVC Tubing	Eurovac Part No.	Description
		CLEAR REINFORCED PVC TUBING Application: • For Thicker Products (ie: Waxes)
	HOS-DOM-DPVC1712	3/4" PVC Clear Braided Hose

Coiled Hoses (For Chemical Dispensing & Air)



Coiled Hoses	Eurovac Part No.	Description
		COILED HOSES (CHEMS & AIR) Equipment Specs: • OD & ID: 3/8"OD & .245"ID • Coil: 1.25" ID • Gun Side: 8" Long End Tail • Drop Side: 16" Long End Tail • End Fittings: 1/4" MPT Swivel Fitting • Working Pressure: 130 PSI • Approx Working Length: 20' - For 25' Coiled Hose • Approx Working Length: 34' - For 40' Coiled Hose Includes: • 1/4" FPT Nipple
	HOS-TPU-C121100D	3/8" OD x 25' Red Polyurethane Coiled Hose • 1st Chem
	HOS-TPU-D121100D	3/8" OD x 25' Blue Polyurethane Coiled Hose • 2nd Chem
	HOS-TPU-F121100D	3/8" OD x 25' Yellow Polyurethane Coiled Hose • 3rd Chem
	HOS-TPU-G121100D	3/8" OD x 25' Orange Polyurethane Coiled Hose • 4th Chem
	HOS-TPU-J121100D	3/8" OD x 25' Green Polyurethane Coiled Hose • 5th Chem
	HOS-TPU-B121100D	3/8" OD x 25' Black Polyurethane Coiled Hose • 6th Chem or Air
	HOS-TPU-H121100D	3/8" OD x 25' Grey Polyurethane Coiled Hose • 7th Chem
	HOS-TPU-I121100D	3/8" OD x 25' White Polyurethane Coiled Hose • 8th Chem
	HOS-TPU-B121100D	3/8" OD x 25' Black Polyurethane Coiled Hose • Air




HOS-TPU-J121100D	3/8" OD x 25' Neon Green Polyurethane Coiled Hose ● 9th Chem
HOS-TPU-K121100D	3/8" OD x 25' Neon Pink Polyurethane Coiled Hose ● 10th Chem
HOS-TPU-L121100D	3/8" OD x 25' Purple Polyurethane Coiled Hose ● 11th Chem
HOS-TPU-M121100D	3/8" OD x 25' Clear Polyurethane Coiled Hose ● 12th Chem
HOS-TPU-N121100D	3/8" OD x 25' Neon Orange Polyurethane Coiled Hose ● 13th Chem
HOS-TPU-O121100D	3/8" OD x 25' Neon Yellow Polyurethane Coiled Hose ● 14th Chem
HOS-TPU-P121100D	3/8" OD x 25' Light Grey Polyurethane Coiled Hose ● 15th Chem
HOS-TPU-C121100F	3/8"OD x 40' Red Polyurethane Coiled Hose ● 1st Chem
HOS-TPU-D121100F	3/8"OD x 40' Blue Polyurethane Coiled Hose ● 2nd Chem
HOS-TPU-F121100F	3/8"OD x 40' Yellow Polyurethane Coiled Hose ● 3rd Chem
HOS-TPU-G121100F	3/8"OD x 40' Orange Polyurethane Coiled Hose ● 4th Chem
HOS-TPU-J121100F	3/8" OD x 40' Green Polyurethane Coiled Hose ● 5th Chem
HOS-TPU-B121100F	3/8"OD x 40' Black Polyurethane Coiled Hose ● 6th Chem or Air
HOS-TPU-H121100F	3/8"OD x 40' Grey Polyurethane Coiled Hose ● 7th Chem
HOS-TPU-I121100F	3/8"OD x 40' White Polyurethane Coiled Hose ● 8th Chem
HOS-TPU-B121100F	3/8"OD x 40' Black Polyurethane Coiled Hose ● Air
HOS-TPU-E121100F	3/8"OD x 40' Neon Green Polyurethane Coiled Hose ● 9th Chem
HOS-TPU-K121100F	3/8" OD x 40' Neon Pink Polyurethane Coiled Hose ● 10th Chem
HOS-TPU-L121100F	3/8" OD x 40' Purple Polyurethane Coiled Hose ● 11th Chem
HOS-TPU-M121100F	3/8" OD x 40' Clear Polyurethane Coiled Hose ● 12th Chem
HOS-TPU-N121100F	3/8" OD x 25' Neon Orange Polyurethane Coiled Hose ● 13th Chem
HOS-TPU-O121100F	3/8" OD x 40' Neon Yellow Polyurethane Coiled Hose ● 14th Chem
HOS-TPU-P121100F	3/8" OD x 40' Light Grey Polyurethane Coiled Hose ● 15th Chem

Double Coiled Hoses	Eurovac Part No.	Description
		DOUBLED COILED HOSES (CHEMS) Application: <ul style="list-style-type: none"> • For Atomizing Applications (converting into a fine particle). One line is for the chemical and one line is for air which turns thicker chemicals into a spray. To be used with Binks spray gun
	HOS-TPW-M35970BB	3/8" OD x 35' Blue/Black Twin Bonded Coiled Hose
	HOS-TPW-M35970RB	3/8" OD x 35' Red/Black Twin Bonded Coiled Hose

Compressed Air Blow Guns



Compact Blow Gun	Eurovac Part No.	Description
		COMPACT BLOW GUN w/ SAFETY TIP Features: <ul style="list-style-type: none"> • Meets OSHA requirements. • Safety tip prevents blockage Equipment Specs: <ul style="list-style-type: none"> • Connection: 1/4 (F) NPT • 200 psi Max
	HOS-BLG-G0B08NA0	Compact Blow Gun w/ Safety Tip
Ergonomic Blow Gun	Eurovac Part No.	Description
		ERGONOMIC POLYMER BLUE BLOW GUN w/ SAFETY VENTURI TIP Features: <ul style="list-style-type: none"> • Maximum safety blow gun which exceed OSHA requirements. If the tip of the nozzle is blocked, a check valve located inside the blow gun mechanism immediately shuts off the airflow. • Airflow can be precisely regulated simply by squeezing and releasing the handle • Convenient built-in ring for easy storage • Ergonomically designed non-slip grip to ensure complete safety and handling • Superior durability thanks to the materials used in the manufacturing • Laboratory tested mechanism to resist to more than 100 000 operation cycles Equipment Specs: <ul style="list-style-type: none"> • Body: Reinforced antishock polyamide • Nozzle: Reinforced antiscratch polyamide • Valve: Reinforced polyamide • Springs: Galvanized steel • Seals: NBR • Connection Inset: Brass • Maximum Working Pressure: 145 PSI • Temperature range: -15 °C to 70 °C • Connection: 1/4 (F) NPT • 7.7 SCFM @ 87 PSI
	HOS-BLG-ERG0BL00	Ergonomic Polymer Blue Blow Gun w/ Safety Venturi Tip

Plastic Chemical Dispensing Gun & Tip



Plastic Dispensing Gun & Tip	Eurovac Part No.	Description
		PLASTIC DISPENSING GUN & TIP Equipment Specs: <ul style="list-style-type: none"> All-plastic Chemical Application Spray Gun Viton seals Inlet - 1/4" Female Pipe Thread Max Operating Pressure: 150psi Max Temperature: 120 deg F Gun Capacity: 2 GPM Tip Capacity: Range of .097 to .90 GPM (depending on the pressure setting) Material: Polypropylene Valve Body Required to Operate: <ul style="list-style-type: none"> Plastic Dispensing Gun & Tip (see below)
	HOS-BLG-22650PP1	Plastic Dispensing Gun
	HOS-BLG-5500PPBX	Plastic Adjustable Conejet Spray Tip

Brass Chemical Dispensing Guns & Tips (Optional PVC Tips)


Brass Dispensing Guns & Tips	Eurovac Part No.	Description
		BRASS DISPENSING GUNS Equipment Specs: <ul style="list-style-type: none"> Inlet/Outlet - 1/4" Female Pipe Thread Buna, Seals Available Up Request Not Included: <ul style="list-style-type: none"> Brass Dispensing Tips (see below)
	HOS-BLG-2542EE3B	Brass (Ethylene Polypropylene Seals) Dispensing Gun <ul style="list-style-type: none"> Stamp Code On Valve: 4E42B
	HOS-BLG-2542FF3B	Brass (Viton Seals) Dispensing Gun <ul style="list-style-type: none"> Stamp Code On Valve: 4FF42-B
	HOS-BLG-2582ET18	Brass (Teflon Disc with Ethylene Propylene O-Ring) Dispensing Gun <ul style="list-style-type: none"> O-Ring NOT available in Teflon
Brass Dispensing Tips	Eurovac Part No.	Description
		BRASS DISPENSING TIPS Equipment Specs: <ul style="list-style-type: none"> 1/4" Male Pipe Thread Spray Angle Degrees Based On 40psi Note: <ul style="list-style-type: none"> .026 Orifice is Standard Tip Not Included: <ul style="list-style-type: none"> Brass Dispensing Gun (see above)
	CLE-JBD-H5080010	Brass 80 Degree .026 Orifice V-Jet Dispensing Tip <ul style="list-style-type: none"> .10 GPM @ 40PSI
	CLE-JBD-H5080020	Brass 80 Degree .036 Orifice V-Jet Dispensing Tip <ul style="list-style-type: none"> .20 GPM @ 40PSI
	CLE-JBD-H5080050	Brass 80 Degree .057 Orifice V-Jet Dispensing Tip <ul style="list-style-type: none"> .50 GPM @ 40PSI

PVC Dispensing Tips	Eurovac Part No.	Description
		PVC DISPENSING TIPS (OPTION TO BRASS) Equipment Specs: <ul style="list-style-type: none"> • 1/4" Male Pipe Thread • Spray Angle Degrees Based On 40psi Note: <ul style="list-style-type: none"> • .026 Orifice Not Available in PVC Not Included: <ul style="list-style-type: none"> • Brass Dispensing Gun (see above)
	CLE-JBD-H505002C	PVC 50 degree (Dark Blue) .036 Orifice V-Jet Dispensing Tip
	CLE-JBD-H508002C	PVC 80 degree (Light Green) .036 Orifice V-Jet Dispensing Tip <ul style="list-style-type: none"> • .20 GPM @ 40PSI
	CLE-JBD-H511002C	PVC 110 degree (Light Blue) .036 Orifice V-Jet Dispensing Tip
Brass Gun Seal Kits	Eurovac Part No.	Description
		BRASS GUN SEAL KITS Includes: <ul style="list-style-type: none"> • Stem & Screw • Disc Cage & Disc • O-Ring • Spring
	HOS-BLG-2542FF34	Viton Seal Replacement Kit - For Brass Gun
	HOS-BLG-252ATF20	Teflon Seal Replacement Kit - For Brass Gun
Brass Gun Parts	Eurovac Part No.	Description
		BRASS GUN REPLACEMENT PARTS
	HOS-BLG-KC600FPM	Viton O-Ring - For Brass Gun
	HOS-BLG-KC101FPM	Viton Disc - For Brass Gun


Stainless Steel Chemical Dispensing Gun & Tips

Stainless Dispensing Gun	Eurovac Part No.	Description
		STAINLESS STEEL DISPENSING GUN Equipment Specs: <ul style="list-style-type: none"> • 303 Stainless Steel w/ Nylon Valve Seat & Viton O-ring • Rated to 150 PSI / 7 GPM / 160 deg F • Inlet - 1/4" Female Pipe Thread Not Included: <ul style="list-style-type: none"> • Stainless Steel Dispensing Tips (see below)
	HOS-BLG-AA3614SS	Stainless Steel Dispensing Gun
Stainless Steel Tips	Eurovac Part No.	Description
		STAINLESS STEEL DISPENSING TIPS Equipment Specs: <ul style="list-style-type: none"> • 1/4" Male Pipe Thread • Spray Angle Degrees Based On 40psi Note: <ul style="list-style-type: none"> • .026 Orifice is Standard Tip Not Included: <ul style="list-style-type: none"> • Stainless Steel Dispensing Gun (see above)
	CLE-JBD-H508001S	Stainless Steel 80 degree .026 Orifice V-Jet Dispensing Tip <ul style="list-style-type: none"> • .10 GPM @ 40PSI


Atomizing Chemical Dispensing Gun

Atomizing Dispensing Guns	Eurovac Part No.	Description
		ATOMIZING DISPENSING GUNS Application: <ul style="list-style-type: none"> • With help of compressed air, a thicker product is reduced to a finer particle which can be sprayed Includes: <ul style="list-style-type: none"> • 63B Fluid Nozzle
	HOS-TPW-2100BINK	Atomizing Dispensing Gun
Atomizing Gun Repair Kit	Eurovac Part No.	Description
		ATOMIZING GUN REPAIR KIT
	HOS-TPW-62290000	Atomizing Gun Repair Kit

Chemical Dispensing Tap

Dispensing Tap	Eurovac Part No.	Description
		DISPENSING TAP Equipment Specs: <ul style="list-style-type: none"> • Inlet - 1/4" NPT
	HOS-CON-14BVR0MA	Dispensing Tap


Extractor Tool Dispensing Tips

Extractor Tips	Eurovac Part No.	Description
		EXTRACTOR TOOL DISPENSING TIPS Equipment Specs: <ul style="list-style-type: none"> • Spray Angle Degrees Based On 40psi Note: <ul style="list-style-type: none"> • .036 Orifice is Standard Tip Includes: <ul style="list-style-type: none"> • O-Ring Not Included: <ul style="list-style-type: none"> • Extractor Tool (See Cleaning Tools Price List)
	CLE-JBD-H5380010	Plastic 80 degree .026" Orifice (Orange) Extractor Tip • .10 GPM @ 40PSI
	CLE-JBD-A4280020	Plastic 80 degree .036" Orifice (Yellow) Extractor Tip • .20 GPM @ 40PSI
	CLE-JBD-H5380040	Plastic 80 degree .052" Orifice (Red) Extractor Tip • .40 GPM @ 40PSI
	CLE-JBD-H5380080	Plastic 80 degree .072" orifice (White) Extractor Tip • .80 GPM @ 40PSI



Extractor Tool Replacement Parts

Extractor Tool Parts	Eurovac Part No.	Description
		EXTRACTOR TOOL REPLACEMENT PARTS Note: <ul style="list-style-type: none"> • For Extractor Tool (See Cleaning Tools Price List)
	CLE-JBD-BAREU156	3 1/2"W S.S. Extractor Tool <ul style="list-style-type: none"> • Stainless Head Only - No Extractor Items Included
	CLE-JBD-V1245000	Cast Aluminum Valve (400psi)
	CLE-JBD-AC31V500	Hanger For U156 Extractor Tool
	CLE-JBD-CFT60000	1/8"MPT x 3/16" Tube Comp Connector
	CLE-JBD-A4266001	Retainer Plate U156 Extractor Tool Includes: <ul style="list-style-type: none"> • QTY 2 - Stainless Steel Fillister HD Screw - 8 32 x 1/4"
	HAR-STM-CDFP0802	8-32 x 1/4" 304 SS Screw 304 <ul style="list-style-type: none"> • Used with Retainer Plate
	HOS-PIN-1604SM02	1/4" Tube x 1/8"MPT NP Brass Push-In Swivel Y Branch
Extractor Tool Alum. Valve Repair Kit	Eurovac Part No.	Description
		EXTRACTOR TOOL ALUMINUM VALVE REPAIR KIT Includes: <ul style="list-style-type: none"> • Valve Hanger (CLE-JBD-AC31V500) • S.S. Pan HD Screw - 10-32 x 1 3/16" Machine • S.S. Nut 10-32 • Valve Stem, Spring and O-rings.
	CLE-JBD-R1245000	400psi Aluminum Valve Repair Kit





Tankless Electric Water Heaters

Electric Heaters	Eurovac Part No.	Description
		<p>TANKLESS ELECTRIC WATER HEATERS</p> <p>General Performance Features:</p> <ul style="list-style-type: none"> • On demand, consistent and continuous hot water • Digital temperature control in increments of 1deg ranging from 80F to 140F • Robust copper immersion heating elements with brass top increases durability and are threaded for easy replacement • Simple installation - 1/2" compression water connections with 1/2" NPT adapters included <p>8KW Heater:</p> <ul style="list-style-type: none"> • Amps: 33A • Recommended Breaker Size: (1x40)A • Recommended Wire Size (CU): 8 AWG • Min. Flow (GPM): .3 • Max. Flow (GPM): 4.8 • Temp Rises (F): 1GPM = 55F, 1.5GRM = 36F, 2GPM = 27F, 2.5GPM = 22F, 3GPM = 18F, 4GPM = 14F <p>13KW Heater:</p> <ul style="list-style-type: none"> • Amps: 54A • Recommended Breaker Size: (1x60)A • Recommended Wire Size (CU): 6 AWG • Min. Flow (GPM): .3 • Max. Flow (GPM): 4.8 • Temp Rises (F): 1GPM = 89F, 1.5GRM = 59F, 2GPM = 44F, 2.5GPM = 36F, 3GPM = 30F, 4GPM = 22F <p>208V 1Ph Note:</p> <ul style="list-style-type: none"> • 240V units can be used on 208V single phase with 25% reduced temperature output. Please note per UL standards the rating plate and installation instructions will all be according to a 240V applied voltage. Check with local officials prior to derating the electrical infrastructure
	HET-08K-24010000	8KW 240V 1Ph Tankless Heater
	HET-13K-24010000	13KW 240V 1Ph Tankless Heater

Return Timer (For Heater & Pump)




Return Timer	Eurovac Part No.	Description
		RETURN TIMER PANEL
	CPA-SPJ-0001024A	Repeat Timer Panel 24-260VAC Type 12 Enclosure
	HOS-ASC-8210G214	<p>2 Way NC GP 1/4" Solenoid Valve 120Vac Coil:</p> <ul style="list-style-type: none"> • Installed into return line • Both pictured items are required to make up this part

Pumps

Flojet Pumps	Eurovac Part No.	Description
		<p>FLOJET PUMPS</p> <p>Equipment Specs:</p> <ul style="list-style-type: none"> • Duplex diaphragm design with automatic demand control • Chemical resistant polypropylene pump housing • Patented shuttle valve eliminates stalling • Air Inlet & Outlet - 1/4" Hose Barb • Fluid Inlet & Outlet - 3/8" Hose Barb Standard (1/2" John Guest Push Lock Available) • Fluid Outlet - 1/4" NPT • Maximum 100PSI Working Pressure • Typically set at approx 45 to 50PSI • Flow rate: 5 GPM • Max CFM: 2.1 @ 100PSI • Recommended usage: water based products
	<p>HOS-SIM-G575205A</p>	<p>Flojet Santoprene Diaphragm Pump</p> <ul style="list-style-type: none"> • Good for wax and wash solutions not containing solvents <p>Allowable Fluids for Santoprene Materials:</p> <ul style="list-style-type: none"> • Portable Water, Acids, Alkaline, Soaps, Alcohols, Ketones <p>NOT Allowable Fluids for Santoprene Materials:</p> <ul style="list-style-type: none"> • Oils, Solvents, Soaps with Solvents, D-Limonene, Aromatic Hydrocarbons
	<p>HOS-SIM-G573205A</p>	<p>Flojet 1/4" Viton Diaphragm Pump</p> <ul style="list-style-type: none"> • Best selection for products containing acids/solvents • For Example: Spot Remover, Tar & Grease Remover, Compounds, Polishes, Waxes, Paint Sealants, Solvent based Fabric Protectants. <p>Allowable Fluids for Viton Materials:</p> <ul style="list-style-type: none"> • Oils, Solvents, D-Limonene, Aromatic & Halogenated Hydrocarbons, Acids <p>NOT Allowable Fluids for Viton Materials:</p> <ul style="list-style-type: none"> • Keytones, Acetones, Automotive Brake Fluid, Ammonia, Ethanol
	<p>HOS-SIM-G57KV000</p>	<p>Flojet 1/4" Kalrez Diaphragm Pump</p> <ul style="list-style-type: none"> • Higher end pump to Santoprene • Best selection for hopeful compatibility if chemical is unknown <p>Allowable Fluids for Kalrez Materials:</p> <ul style="list-style-type: none"> • Lubricating Oils, Hydraulic Oils, Vegetable Oils, Alcohols, Keytones, Aromatic Hydrocarbons, Aliphatic Hydrocarbons, Diluted Acids, Alkalis, Soaps with Solvents, Automotive Brake Fluid, Acetones, Ethanol, Inks <p>NOT Allowable Fluids for Kalrez Materials:</p> <ul style="list-style-type: none"> • Halogenated Solvents
FloJet Pump - Replacement Parts	Eurovac Part No.	Description
		<p>FLOJET PUMP - REPLACEMENT PARTS</p>
	<p>HOS-FLO-20740022</p>	<p>FloJet Check Valve Kit</p>
	<p>HOS-FLO-21000661</p>	<p>FloJet Diaphragm Kit</p>
	<p>HOS-FLO-20751002</p>	<p>FloJet Shaft & Slide Kit</p>
		<p>O-Ring Kit</p>



Aro 1/2" Pumps	Eurovac Part No.	Description
		ARO 1/2" PUMPS Equipment Specs: <ul style="list-style-type: none"> • Maximum flow rates - achieved at 100PSI inlet pressure - high-volume transfer can be achieved at much lower air inlet pressure • Twin-diaphragm design with reciprocating pump action assures smooth, continuous delivery with minimal pulse • Polypropylene pump construction • Air Inlet - 1/4" • Fluid Inlet & Outlet - 1/2" • Maximum 100PSI • Flow rate: 13 GPM • Will handle thicker chemical products (use 3/4" line and fittings for less friction loss and back pressure)
	HOS-ARO-66605J38	Aro 1/2" Air Diaphragm Pump - Urethane <ul style="list-style-type: none"> • Best selection for neutral pH wash solutions
	HOS-ARO-66605J34	Aro 1/2" Air Diaphragm Pump - Santoprene <ul style="list-style-type: none"> • Best selection for wax and wash solutions not containing acid • Used for Ziebart's thick wax product (requires 3/4" chem line for transferring chemical to Binks gun for adomization)
	HOS-ARO-66605J34	Aro 1/2" Air Diaphragm Pump - Teflon <ul style="list-style-type: none"> • Best selection for products containing acid • Higher end - most chemically compatible across the board
Aro 1/2" Pump - Replacement Parts	Eurovac Part No.	Description
		ARO 1/2" PUMP - REPLACEMENT PARTS
	HOS-ARO-63714044	ARO (Teflon) Repair Kit - For HOS-ARO-66605534
	HOS-ARO-63714100	ARO Air Section Repair Kit - For All 1/2" ARO Pumps
Air Regulator for Pumps	Eurovac Part No.	Description
		AIR REGULATOR
	HOS-FRL-AR200012	1/4" Air Regulator c/w Gauge & Mounting Bracket

Poly Fittings

Poly Fittings	Eurovac Part No.	Description
		POLY FITTINGS
	HOS-PIP-0250SOVL	1/4" Black Poly Shut-off Valve
	HOS-PIP-0375SOVL	3/8" Black Poly Shut-off Valve
	HOS-PIP-0U005003	3/8" x 1/4" Tube Black Poly Push in Reducing Union
	HOS-PIP-0U006005	1/2" x 3/8" Tube Black Poly Push in Reducing Union
	MPF-TBL-002PLAST	3/8" Push in Gray Bulkhead Union



	HOS-PIP-0U005005	3/8" x 3/8" Tube Black Poly Push in Union
	HOS-PIP-0E005005	3/8" x 3/8" Tube Black Poly Push In 90 Elbow
	HOS-PIP-0E006006	1/2" x 1/2" Tube Black Poly Push in 90 Elbow
	HOS-PIP-TK005003	3/8" Tube x 1/4" MNPT Black Poly Push in Connector
	HOS-PIP-TK005006	3/8" Tube x 1/2" MNPT Black Poly Push in Connector
	HOS-PIP-TK006005	1/2" Tube x 3/8" MNPT Gray Poly Push in Connector
	HOS-PIP-TK006006	1/2" Tube x 1/2" MNPT Gray Poly Push in Connector
	HOS-PIP-0T005005	3/8" x 3/8" x 3/8" Tube Black Poly Push in Tee
	HOS-PIP-0T006006	1/2" x 1/2" x 1/2" Tube Gray Poly Push in Tee
	HOS-PIP-D2716B00	3/8" Gray Poly Push in Tee - 1/4" MPT On Run
	HOS-PIP-TE005003	3/8" Tube x 1/4" MPT Tube Gray Poly Push in 90 Elbow

Brass Fittings



Brass Fittings	Eurovac Part No.	Description
		BRASS FITTINGS Note: <ul style="list-style-type: none"> • Every compression fitting that is going to tubing requires one insert & one sleeve • 3/4" Tee required for thicker waxes
	MPF-BRV-NSF00003	1/4" FPT Brass Needle Valve Straight • Flow Control Valve
	MPF-BRC-0U005003	3/8" x 1/4" Tube Brass Compression Reducing Union
	MPF-BRC-0U006005	1/2" x 3/8" Tube Brass Compression Reducing Union

	MPF-BRC-OU005005	3/8" x 3/8" Tube Brass Compression Union
	MPF-BRC-OU006006	1/2" x 1/2" Tube Brass Compression Union
	MPF-BRC-OE005005	3/8" x 3/8" Tube Brass Compression 90 Elbow
	MPF-BRC-OE006006	1/2" x 1/2" Tube Brass Compression 90 Elbow
	MPF-BRC-TK005003	3/8" Tube x 1/4" MNPT Brass Compression Connector
	MPF-BRC-TK006003	1/2" Tube x 1/4" MNPT Brass Compression Connector
	MPF-BRC-TK006005	1/2" Tube x 3/8" MNPT Brass Compression Connector
	MPF-BRC-TK006006	1/2" Tube x 1/2" MNPT Brass Compression Connector
	MPF-BRC-OT005005	3/8" x 3/8" x 3/8" Tube Brass Compression Tee
	MPF-BRC-OT006006	1/2" x 1/2" x 1/2" Tube Brass Compression Tee
	HOS-PIN-01040M04	1/4" Tube x 1/4" MNPT NP Brass Push-In Connector
	MPF-BRC-0I005000	3/8" Tube Size Brass Insert for Non-Metallic Tubing
	MPF-BRC-0I006000	1/2" Tube Size Brass Insert for Non-Metallic Tubing
	MPF-BRC-0S005MAR	3/8" Tube Sleeve Molded Acetal Resin
	MPF-BRC-0S006MAR	1/2" Tube Sleeve Molded Acetal Resin
	MPF-BRE-NTTF0070	3/4" FPT Brass Tee
	HOS-BBR-00090M09	3/4" ID Hose x 3/4" MPT Hose Barb Brass • QTY 3 Required For Every Brass Tee
	HOS-BBR-00080008	3/4" ID Hose x 3/4" ID Hose Barb Brass Splicer
	HOS-CLS-SE011600	Tight Seal Heavy Duty Clamp 1" to 1-1/16" ID Hose 430 SS • QTY 3 Required For Every Brass Tee
	MPF-TBL-002BRASS	1/4" NPT Terminal Block - Brass Application: • Pendant Drops • Incoming Air on Chemical Dispensing System • Heated Extractor Return Line on Chemical Dispensing System
	MPF-TBL-003BRASS	3/8" NPT Terminal Block - Brass Application: • Incoming Water on Chemical Dispensing System
	MPF-TBL-004BRASS	1/2" NPT Terminal Block - Brass
	MPF-BRE-NTPA0702	1/4" MPT x 1/2" FPT Brass Pipe Adaptor


Brass Extractor Work Stations


Extractor Work Stations	Eurovac Part No.	Description
		EXTRACTOR WORK STATIONS
	SYS-SUB-EXSINGLE	Single Drop Heated Extractor Assembly
	SYS-SUB-EXDOUBLE	Double Drop Heated Extractor Assembly

Insulation For Extractor Line

Insulation	Eurovac Part No.	Description
		INSULATION
	PPF-INS-00050600	1/2" x 6' Pipe Insulation - Priced Per Each
Ball Valve		
Ball Valve	Eurovac Part No.	Description
		BALL VALVE
	HOS-CON-14BV0000	1/4" FPT Bronze Ball Valve

Proportioners For Squeeze Bottles & Filling Buckets


1 Chemical Proportioner - 4.8GPM	Eurovac Part No.	Description																																																												
		<p>1 CHEM PROPORTIONER - 4.8 GPM</p> <p>Equipment Specs:</p> <ul style="list-style-type: none"> • Drum or wall mounted • Proportioner automatically mixes liquid cleaning and sanitizing concentrates with water and dispenses the diluted solution into any container. • Any size container of concentrate can be used with this proportioner because there's no need to tip the container to pour the contents. • Uses water power, not electricity, so concentrates don't have to be located near outlets, just within a hose's reach of a water source. • 40PSI Water Pressure is optimal • 4.8 Gallons Per Minute • Only for water thin products <p>Assumptions:</p> <ul style="list-style-type: none"> • Dilutions based on 40 psi water pressure <p>Includes:</p> <ul style="list-style-type: none"> • Drum proportioner • Suction tube (4 ft.) with foot valve • Metering tips (14 tips) with dilution options range from 1:1 to 110:1 																																																												
	SYS-020-1C206000	<p>1 Chemical High Concentration Proportioner From Large Totes</p>																																																												
		<table border="1"> <thead> <tr> <th>TIP COLOR</th> <th>SIZE</th> <th>DRILL NUMBER</th> <th>RATIO</th> </tr> </thead> <tbody> <tr> <td>• No Tip</td> <td></td> <td></td> <td>4.5:1</td> </tr> <tr> <td>• Gray</td> <td>.128</td> <td>(30)</td> <td>5:1</td> </tr> <tr> <td>• Black</td> <td>.098</td> <td>(40)</td> <td>6:1</td> </tr> <tr> <td>• Beige</td> <td>.070</td> <td>(50)</td> <td>9:1</td> </tr> <tr> <td>• Red</td> <td>.052</td> <td>(55)</td> <td>20:1</td> </tr> <tr> <td>• White</td> <td>.043</td> <td>(57)</td> <td>24:1</td> </tr> <tr> <td>• Blue</td> <td>.040</td> <td>(60)</td> <td>26:1</td> </tr> <tr> <td>• Tan</td> <td>.035</td> <td>(65)</td> <td>31:1</td> </tr> <tr> <td>• Green</td> <td>.028</td> <td>(70)</td> <td>50:1</td> </tr> <tr> <td>• Orange</td> <td>.025</td> <td>(72)</td> <td>70:1</td> </tr> <tr> <td>• Brown</td> <td>.023</td> <td>(74)</td> <td>90:1</td> </tr> <tr> <td>• Yellow</td> <td>.020</td> <td>(76)</td> <td>100:1</td> </tr> <tr> <td>• Purple</td> <td>.014</td> <td>(79)</td> <td>200:1</td> </tr> <tr> <td>• Pink</td> <td>.010</td> <td>(87)</td> <td>400:1</td> </tr> </tbody> </table>	TIP COLOR	SIZE	DRILL NUMBER	RATIO	• No Tip			4.5:1	• Gray	.128	(30)	5:1	• Black	.098	(40)	6:1	• Beige	.070	(50)	9:1	• Red	.052	(55)	20:1	• White	.043	(57)	24:1	• Blue	.040	(60)	26:1	• Tan	.035	(65)	31:1	• Green	.028	(70)	50:1	• Orange	.025	(72)	70:1	• Brown	.023	(74)	90:1	• Yellow	.020	(76)	100:1	• Purple	.014	(79)	200:1	• Pink	.010	(87)	400:1
TIP COLOR	SIZE	DRILL NUMBER	RATIO																																																											
• No Tip			4.5:1																																																											
• Gray	.128	(30)	5:1																																																											
• Black	.098	(40)	6:1																																																											
• Beige	.070	(50)	9:1																																																											
• Red	.052	(55)	20:1																																																											
• White	.043	(57)	24:1																																																											
• Blue	.040	(60)	26:1																																																											
• Tan	.035	(65)	31:1																																																											
• Green	.028	(70)	50:1																																																											
• Orange	.025	(72)	70:1																																																											
• Brown	.023	(74)	90:1																																																											
• Yellow	.020	(76)	100:1																																																											
• Purple	.014	(79)	200:1																																																											
• Pink	.010	(87)	400:1																																																											

1 Chemical Proportioner - 2.5GPM	Eurovac Part No.	Description																																												
		<p>1 CHEM PROPORTIONER - 2.5 GPM</p> <p>Equipment Specs:</p> <ul style="list-style-type: none"> • Drum or wall mounted • Proportioner automatically mixes liquid cleaning and sanitizing concentrates with water and dispenses the diluted solution into any container. • Any size container of concentrate can be used with this proportioner because there's no need to tip the container to pour the contents. • Uses water power, not electricity, so concentrates don't have to be located near outlets, just within a hose's reach of a water source. • 40PSI Water Pressure is optimal • 2.5. Gallons Per Minute • Capable of pulling thicker products than SYS-020-1C206000 <p>Assumptions:</p> <ul style="list-style-type: none"> • Dilutions based on 40 psi water pressure <p>Includes:</p> <ul style="list-style-type: none"> • Drum proportioner • Suction tube (4 ft.) with foot valve • Metering tips (14 tips) with dilution options range from 1:1 to 110:1 																																												
	SYS-020-1C208000	1 Chemical Proportioner From Large Totes																																												
		<table border="1"> <thead> <tr> <th>TIP COLOR</th> <th>SIZE / DRILL NUMBER</th> <th>RATIO</th> </tr> </thead> <tbody> <tr><td>• No Tip</td><td>.187 (3/16)</td><td>1:1</td></tr> <tr><td>• Gray</td><td>.128 (30)</td><td>1.3:1</td></tr> <tr><td>• Black</td><td>.098 (40)</td><td>2:1</td></tr> <tr><td>• Beige</td><td>.070 (50)</td><td>3.5:1</td></tr> <tr><td>• Red</td><td>.052 (55)</td><td>6:1</td></tr> <tr><td>• White</td><td>.043 (57)</td><td>9:1</td></tr> <tr><td>• Blue</td><td>.040 (60)</td><td>10:1</td></tr> <tr><td>• Tan</td><td>.035 (65)</td><td>13:1</td></tr> <tr><td>• Green</td><td>.028 (70)</td><td>18:1</td></tr> <tr><td>• Orange</td><td>.025 (72)</td><td>25:1</td></tr> <tr><td>• Brown</td><td>.023 (74)</td><td>30:1</td></tr> <tr><td>• Yellow</td><td>.020 (76)</td><td>37:1</td></tr> <tr><td>• Purple</td><td>.014 (79)</td><td>55:1</td></tr> <tr><td>• Pink</td><td>.010 (87)</td><td>110:1</td></tr> </tbody> </table>	TIP COLOR	SIZE / DRILL NUMBER	RATIO	• No Tip	.187 (3/16)	1:1	• Gray	.128 (30)	1.3:1	• Black	.098 (40)	2:1	• Beige	.070 (50)	3.5:1	• Red	.052 (55)	6:1	• White	.043 (57)	9:1	• Blue	.040 (60)	10:1	• Tan	.035 (65)	13:1	• Green	.028 (70)	18:1	• Orange	.025 (72)	25:1	• Brown	.023 (74)	30:1	• Yellow	.020 (76)	37:1	• Purple	.014 (79)	55:1	• Pink	.010 (87)
TIP COLOR	SIZE / DRILL NUMBER	RATIO																																												
• No Tip	.187 (3/16)	1:1																																												
• Gray	.128 (30)	1.3:1																																												
• Black	.098 (40)	2:1																																												
• Beige	.070 (50)	3.5:1																																												
• Red	.052 (55)	6:1																																												
• White	.043 (57)	9:1																																												
• Blue	.040 (60)	10:1																																												
• Tan	.035 (65)	13:1																																												
• Green	.028 (70)	18:1																																												
• Orange	.025 (72)	25:1																																												
• Brown	.023 (74)	30:1																																												
• Yellow	.020 (76)	37:1																																												
• Purple	.014 (79)	55:1																																												
• Pink	.010 (87)	110:1																																												




Proportioner Parts

Proportioner Parts	Eurovac Part No.	Description
		PROPORTIONER PARTS
	SYS-HYD-50080000	Proportioner - 1/4" ID Vinyl Flexible Tubing (per ft.) • Purchase per foot or 100' lengths
	SYS-HYD-69001400	Proportioner - Standard Push In Tip Kit
	SYS-HYD-90031210	Proportioner - Ultra Lean Push In Tip Kit

Hydrominders




Hydrominders	Eurovac Part No.	Description
		HYROMINDERS Equipment Specs: <ul style="list-style-type: none"> • Spray Angle Degrees Based On 40psi Note: <ul style="list-style-type: none"> • 515 Is Standard On All CDC Systems
	SYS-HYD-05150000	Hydrominder 515 1.5 GPM Soap Mixer <ul style="list-style-type: none"> • Brown Eductor Valve
	SYS-HYD-05110000	Hydrominder 511 4.5 GPM Soap Mixer <ul style="list-style-type: none"> • Black Eductor Valve
	SYS-HYD-05320000	Hydrominder 532 Dual Eductor (Two 511's) 4.5 GPM Soap Mixer



Hydrominder Parts

Hydrominder Parts	Eurovac Part No.	Description
		HYROMINDER PARTS
	SUB-020-CDPAC000	12" Plastic White Pail & Lid w/ SS Plate - For 511 & 515
	SUB-020-CDPAC532	12" Plastic White Pail & Lid w/ SS Plate - For 532
	SYS-HYD-23810000	Strainer Washer (No. 1) <ul style="list-style-type: none"> • For Hydrominder #511 & #515
	SYS-HYD-36090000	Nipple (No. 4) <ul style="list-style-type: none"> • For Hydrominder #511 & #515
	SYS-HYD-10080500	Magnet Parts Kit (No. 5) <ul style="list-style-type: none"> • For Hydrominder #511 & #515

	SYS-HYD-66552000	Valve Parts Kit (No. 7) <ul style="list-style-type: none"> • For Hydrominder #511 & #515 • Former part number was 6655-P (same item)
	SYS-HYD-52000000	Water Valve Body (No. 8) <ul style="list-style-type: none"> • For Hydrominder #511 & #515
	HOS-GRA-2A646000	Flomatic 3/4" Foot Valve
	SYS-HYD-10092530	Hydrominder Vacuum Breaker #511 & #515
	SYS-HYD-10076302	Bucket Strainer - For Hydrominder
	SYS-HYD-50589A00	1/2" x 9' Suction Tube w/ Ceramic Weight
	SYS-HYD-10076301	Blue Foot Valve w/ Strainer
	SYS-HYD-69001500	Metering Tip Kit, Threaded

Inline Water Filters

Inline Water Filters	Eurovac Part No.	Description
		INLINE WATER FILTER - FOR CHEMICAL DISPENSING SYSTEM
	SUB-020-00WF0700	3/4" Port Water Filter Housing Only (No Filter)
	SUB-020-00WF07RC	2-3/8"x 9-7/8" 5 Micron Filter Cartridge
		HIGH END INLINE WATER FILTER - HEATED EXTRACTOR (RETURN LINE) Equipment Specs: <ul style="list-style-type: none"> • Flow Range: Up to 150 GPM • Max Pressure: 100 PSI • Max Temperature: 120 F • Filter Element: 60 mesh (250 microns) Product Benefits: <ul style="list-style-type: none"> • Reverse flush technology actually reverses the flow of water to push all of the dirt off and out of the filter • No need to take the filter apart to scrub the mesh - simply twist and clean • A larger filter element means more time between flushes • Durable stainless-steel screen • Viton O-Ring at Flush Port means maximum strength for a longer life of the filter
	SYS-020-HEWF0700	Twist II Clean Inline Water Filter Assembly - 3/4" NPT Inlet/Outlet

	SUB-020-HEWFBOWL	Bowl & O-Ring Kit (Replacement Part)
	SUB-020-HEWFFILT	Filter Element (Replacement Part)

Chemicals

Chemicals	Eurovac Part No.	Description
		CHEMICALS
	CHE-PLA-5G00000C	Plastic & Vinyl Cleaner - 5 Gallon <ul style="list-style-type: none"> • Transmate: Kleens #TM091 05 (Ratio: 10:1) • Carbrite: Blue Max #CB00E004-05-S5 (Ratio: 8:1)
	CHE-PLA-55G0000C	Plastic & Vinyl Cleaner - 55 Gallon <ul style="list-style-type: none"> • Transmate: Kleens #TM091 55 (Ratio: 10:1)
	CHE-ENG-5G00000C	Engine Cleaner - 5 Gallon <ul style="list-style-type: none"> • Transmate: Grease Buster #TM116 05 (Ratio: 4:1) • Carbrite: Power Brite #CB00E042-05-S5 (Ratio: 5:1)
	CHE-ENG-55G0000C	Engine Cleaner - 55 Gallon <ul style="list-style-type: none"> • Transmate: Grease Buster #TM116 55 (Ratio: 4:1)
	CHE-WAX-1G04000R	Car Wax - 1 Gallon (Pkg of 4) (Ready To Use) <ul style="list-style-type: none"> • Transmate: Final Detail #TM094 01 (RTU) • Carbrite: Snappy Shine #CBOOA018-03 (RTU)
	CHE-WAX-5G00000R	Car Wax - 5 Gallon (Ready To Use) <ul style="list-style-type: none"> • Transmate: Final Detail #TM094 05 (RTU)
	CHE-GLA-1G04000R	Glass Cleaner - 1 Gallon (Pkg of 4) (Ready To Use) <ul style="list-style-type: none"> • Transmate: Glass Action #TM087 01 (RTU) • Carbrite: Glass Cleaner #CBOOE08A03 (RTU)
	CHE-GLA-5G00000C	Glass Cleaner - 5 Gallon <ul style="list-style-type: none"> • Transmate: Glass Cleaner #TM084 05 (Ratio: 10:1)
	CHE-GLA-5G00000R	Glass Cleaner - 5 Gallon (Ready To Use) <ul style="list-style-type: none"> • Transmate: Glass Action #TM087 05 (RTU)
	CHE-GLA-55G0000C	Glass Cleaner - 55 Gallon <ul style="list-style-type: none"> • Transmate: Glass Cleaner #TM084 55 (Ratio: 10:1)
	CHE-EXT-5G00000C	Extractor Shampoo - 5 Gallon <ul style="list-style-type: none"> • Typically heated • Transmate: Extractor Shampoo #TM115 05 (Ratio: 24:1) • Carbrite: Extractor HD #CBOOE045-05-S5 (Ratio: 24:1)
	CHE-EXT-55G0000C	Extractor Shampoo - 55 Gallon <ul style="list-style-type: none"> • Typically heated • Transmate: Extractor Shampoo #TM115 55 (Ratio: 24:1)



CHE-DRE-1G04000R	Tire Dressing - 1 Gallon (Pkg of 4) (Ready To Use) <ul style="list-style-type: none"> ● Transmate: Black Pearl #TM122 01 (RTU)
CHE-DRE-5G00000C	Tire Dressing - 5 Gallon <ul style="list-style-type: none"> ● Transmate: Unique #TM107 05 (Ratio: 1:1) ● Carbrite: Max Gloss #CBOOC045G05-S5 (Ratio: 1:1)
CHE-DRE-55G0000C	Tire Dressing - 55 Gallon <ul style="list-style-type: none"> ● Transmate: Unique #TM107 55 (Ratio: 1:1)
CHE-DRE-5G00000R	Tire Dressing - 5 Gallon (Ready To Use) <ul style="list-style-type: none"> ● Transmate: Black Pearl #TM122 05 (RTU)
CHE-DRE-55G0000R	Tire Dressing - 55 Gallon (Ready To Use) <ul style="list-style-type: none"> ● Transmate: Black Pearl #TM122 55 (RTU)
CHE-STA-5G00000C	Stain Remover - 5 Gallon <ul style="list-style-type: none"> ● Transmate: PreSpray #TM121 05 (Ratio: 8:1) ● Carbrite: Brite Spot #CBOOE050-05-S5 (Ratio: 4:1)
CHE-STA-55G0000C	Stain Remover - 55 Gallon <ul style="list-style-type: none"> ● Transmate: PreSpray #TM121 55 (Ratio: 8:1)
CHE-WHE-5G00000C	Wheel Cleaner - 5 Gallon <ul style="list-style-type: none"> ● Transmate: Green Monster #TM117 05 (Ratio: 3:1) ● Carbrite: Wheel Cleaner #CBOOE013F05-S5 (Ratio: 4:1)
CHE-WHE-5G00000R	Wheel Cleaner - 5 Gallon (Ready To Use) <ul style="list-style-type: none"> ● Transmate: Brute Force #TM087-05 (RTU)
CHE-WHE-55G0000C	Wheel Cleaner - 55 Gallon <ul style="list-style-type: none"> ● Transmate: Green Monster #TM117 05 (Ratio: 3:1)
CHE-BUG-5G00000C	Bug Remover - 5 Gallon <ul style="list-style-type: none"> ● Transmate: Break Down #TM085 05 (Ratio: 8:1) ● Carbrite: Bug Remover Concentrate #CBOOE003C05-S5 (Ratio: 10:1)
CHE-BUG-55G0000C	Bug Remover - 55 Gallon <ul style="list-style-type: none"> ● Transmate: Break Down #TM085 55 (Ratio: 8:1)
CHE-ALL-5G00000C	All Purpose Cleaner - 5 Gallon <ul style="list-style-type: none"> ● Transmate: Sure Clean #TM092 05 (Ratio: TBD)
CHE-PRE-5G00000C	Pre-Treatment - 5 Gallon <ul style="list-style-type: none"> ● Apply, let product sit for 10 minutes then extract ● Carpet Spot Remover is other known name ● Transmate: Pre-Spray Spotter #TM121 05 (Ratio: 10:1) ● Carbrite: Brite Spot #CBOOE050-05-S5 (Ratio: 30:1)
CHE-PRE-55G0000C	Pre-Treatment - 55 Gallon <ul style="list-style-type: none"> ● Apply, let product sit for 10 minutes then extract ● Carpet Spot Remover is other known name ● Transmate: Pre-Spray Spotter #TM121 55 (Ratio: 10:1)
CHE-CAR-5G00000C	Car Wash Soap - 5 Gallon <ul style="list-style-type: none"> ● Transmate: Hi-Suds #TM006 05
CHE-CAR-55G0000C	Car Wash Soap - 55 Gallon <ul style="list-style-type: none"> ● Transmate: Hi-Suds #TM006 55
CHE-DES-5G00000R	Descaler - 5 Gallon <ul style="list-style-type: none"> ● Helps remove build up in lines